





MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



Tapered Bore - 1:12
Open



Tapered Bore - 1:12
Two Seals
2RS

DEEP GROOVE BALL BEARINGS - TAPERED BORE

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	FAG SKF STEYR	Interchange	
	d	D	B			MRC	RIV
6204-K	20	47	14	.230	6204 K	-	1 AK
6205-K	25	52	15	.280	6205 K	205-SX	2 AK
6206-K	30	62	16	.420	6206 K	206-SX	3 AK
6207-K	35	72	17	.630	6207 K	207-SX	4 AK
6208-K	40	80	18	.780	6208 K	208-SX	5 AK
6209-K	45	85	19	.900	6209 K	209-SX	6 AK
6210-K	50	90	20	1.010	6210 K	210-SX	7 AK
6211-K	55	100	21	1.320	6211 K	211-SX	8 AK
6212-K	60	110	22	1.720	6212 K	-	9 AK
6213-K	65	120	23	2.180	6213 K	213-SX	10 AK
6214-K	70	125	24	2.340	6214 K	214-SX	11 AK
6215-K	75	130	25	2.540	6215 K	215-SX	12 AK
6216-K	80	140	26	3.090	6216 K	216-SX	13 AK
6217-K	85	150	28	4.060	6217 K	217-SX	14 AK
6218-K	90	160	30	4.940	6218 K	218-SX	15 AK
6219-K	95	170	32	6.100	6219 K	-	16 AK
6220-K	100	180	34	7.140	6220 K	220-SX	17 AK
6221-K	105	190	36	8.660	6221 K	221-SX	18 AK
6222-K	110	200	38	10.100	6222 K	222-SX	19 AK
6224-K	120	215	40	12.100	6224-K	-	20 AK
6226-K	130	230	40	13.800	6226 K	-	21 AK
6228-K	140	250	42	17.600	6228 K	-	22 AK
6230-K	150	270	45	25.200	6230 K	-	23 AK
6232-K	160	290	48	31.500	6232 K	-	24 AK
6234-K	170	310	52	38.600	6234 K	-	25 AK
6236-K	180	320	52	40.300	6236 K	-	26 AK
6238-K	190	340	55	50.700	6238 K	-	27 AK
6240-K	200	360	58	62.200	6240 K	-	28 AK

TAPERED BORE - TWO SEALS


6204-K 2RS	20	47	14	.240	6204 K.2RS	-	-
6205-K 2RS	25	52	15	.280	6205 K.2RS	-	-
6206-K 2RS	30	62	16	.440	6206 K.2RS	206-SZZX	-
6207-K 2RS	35	72	17	.640	6207 K.2RS	207-SZZX	-
6208-K 2RS	40	80	18	.820	6208 K.2RS	208-SZZX	-
6209-K 2RS	45	85	19	.900	6209 K.2RS	209-SZZX	-
6210-K 2RS	50	90	20	1.020	6210 K.2RS	210-SZZX	-
6211-K 2RS	55	100	21	1.320	6211 K.2RS	211-SZZX	-
6212-K 2RS	60	110	22	1.730	6212 K.2RS	212-SZZX	-
6213-K 2RS	65	120	23	2.150	6213 K.2RS	213-SZZX	-
6214-K 2RS	70	125	24	2.360	6214 K.2RS	214-SZZX	-
6215-K 2RS	75	130	25	2.650	6215 K.2RS	215-SZZX	-
6216-K 2RS	80	140	26	3.090	6216 K.2RS	216-SZZX	-
6217-K 2RS	85	150	28	3.950	6217 K.2RS	217-SZZX	-
6218-K 2RS	90	160	30	4.940	6218 K.2RS	218-SZZX	-
6219-K 2RS	95	170	32	6.100	6219 K.2RS	219-SZZX	-
6220-K 2RS	100	180	34	7.140	6220 K.2RS	220-SZZX	-

NOTE:

1.) C/3 and C/4 internal clearances are available on all of the above sizes.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



Open With
Snap Ring

DEEP GROOVE BALL BEARINGS - WITH SNAP RING


MVB No.	Dimensions (Metric)		Dimensions (Inch)		Approx. Wgt. (lbs.)	Interchange					
	d	D	B	f		c	FAF	FAG STEYR	MRC	ND	SKF
6200 NR	10	30	9	.134	.053	.080	-	6200 NR	200-SG	43200	6200 NR
6201 NR	12	32	10	.134	.053	.090	201KG	6201 NR	-	43201	6201 NR
6202 NR	15	35	11	.134	.053	.100	202KG	6202 NR	202-SG	43202	6202 NR
6203 NR	17	40	12	.134	.053	.150	203KG	6203 NR	203-SG	43203	6203 NR
6204 NR	20	47	14	.149	.053	.250	204KG	6204 NR	204-SG	43204	6204 NR
62/22 NR	22	50	14	.149	.053	.270	-	-	-	-	-
6205 NR	25	52	15	.149	.053	.290	205KG	6205 NR	205-SG	43205	6205 NR
62/28 NR	28	58	16	.149	.053	.370	-	-	-	-	-
6206 NR	30	62	16	.203	.075	.440	206KG	6206 NR	206-SG	43206	6206 NR
62/32 NR	32	65	17	.203	.075	.550	-	-	-	-	-
6207 NR	35	72	17	.203	.075	.640	207KG	6207 NR	207-SG	43207	6207 NR
6208 NR	40	80	18	.203	.075	.810	208KG	6208 NR	208-SG	43208	6208 NR
6209 NR	45	85	19	.203	.075	.900	209KG	6209 NR	209-SG	43209	6209 NR
6210 NR	50	90	20	.235	.106	1.020	210KG	6210 NR	210-SG	43210	6210 NR
6211 NR	55	100	21	.235	.106	1.340	211KG	6211 NR	211-SG	43211	6211 NR
6212 NR	60	110	22	.235	.106	1.730	212KG	6212 NR	212-SG	43212	6212 NR
6213 NR	65	120	23	.281	.122	2.180	-	6213 NR	213-SG	43213	6213 NR
6214 NR	70	125	24	.281	.122	2.360	214KG	6214 NR	214-SG	43214	6214 NR
6215 NR	75	130	25	.281	.122	2.600	-	6215 NR	215-SG	43215	6215 NR
6216 NR	80	140	26	.313	.122	3.090	-	6216 NR	216-SG	43216	6216 NR
6217 NR	85	150	28	.313	.122	3.950	-	6217 NR	-	43217	6217 NR
6218 NR	90	160	30	.313	.122	4.740	-	6218 NR	-	43218	6218 NR
6219 NR	95	170	32	.361	.138	5.780	-	6219 NR	-	43219	6219 NR
6220 NR	100	180	34	.361	.138	6.920	-	6220 NR	-	43220	6220 NR
6221 NR	105	190	36	.361	.138	8.160	-	6221 NR	-	-	6221 NR
6222 NR	110	200	38	.361	.138	9.610	-	6222 NR	-	43222	6222 NR
6224 NR	120	215	40	.361	.138	12.100	-	6224 NR	-	-	6224 NR
6226 NR	130	230	40	.433	.177	13.800	-	6226 NR	-	-	6226 NR

NOTE:


1.) C/3 and C/4 internal clearances are available on all of the above sizes.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



One Shield
Z



Two Shields
ZZ

DEEP GROOVE BALL BEARINGS - ONE SHIELD

MVB No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	Interchange						
	d	D	B		FAG SKF STEYR	FAF	FED	MRC	ND	NH	RIV
6200-Z	10	30	9	.080	6200 Z	200KD	1200F	200-SF	7500	200P	04 APL
6201-Z	12	32	10	.090	6201 Z	201KD	1201F	201-SF	7501	201P	03 APL
6202-Z	15	35	11	.100	6202 Z	202KD	1202F	202-SF	7502	202P	02 APL
6203-Z	17	40	12	.150	6203 Z	203KD	1203F	203-SF	7503	203P	01 APL
6204-Z	20	47	14	.250	6204 Z	204KD	1204F	204-SF	7504	204P	1 APL
6205-Z	25	52	15	.290	6205 Z	205KD	1205F	205-SF	7505	205P	2 APL
6206-Z	30	62	16	.440	6206 Z	206KD	1206F	206-SF	7506	206P	3 APL
6207-Z	35	72	17	.640	6207 Z	207KD	1207F	207-SF	7507	207P	4 APL
6208-Z	40	80	18	.810	6208 Z	208KD	1208F	208-SF	7508	208P	5 APL
6209-Z	45	85	19	.900	6209 Z	209KD	1209F	209-SF	7509	209P	6 APL
6210-Z	50	90	20	1.020	6210 Z	210KD	1210F	210-SF	7510	210P	7 APL
6211-Z	55	100	21	1.340	6211 Z	211KD	1211F	211-SF	7511	211P	8 APL
6212-Z	60	110	22	1.730	6212 Z	212KD	1212F	212-SF	7512	212P	9 APL
6213-Z	65	120	23	2.180	6213 Z	213KD	1213F	213-SF	7513	213P	10 APL
6214-Z	70	125	24	2.360	6214 Z	214KD	1214F	214-SF	7514	214P	11 APL
6215-Z	75	130	25	2.600	6215 Z	215KD	1215F	215-SF	7515	215P	12 APL
6216-Z	80	140	26	3.090	6216 Z	216KD	1216F	216-SF	7516	216P	13 APL
6217-Z	85	150	28	3.950	6217 Z	217KD	1217F	217-SF	7517	217P	14 APL
6218-Z	90	160	30	4.740	6218 Z	218KD	1218F	218-SF	7518	218P	15 APL
6219-Z	95	170	32	5.780	6219 Z	219KD	1219F	219-SF	7519	219P	16 APL
6220-Z	100	180	34	6.920	6220 Z	220KD	1220F	220-SF	7520	220P	17 APL
6221-Z	105	190	36	8.160	6221 Z	221KD	1221F	221-SF	7521	221P	18 APL
6222-Z	110	200	38	9.610	6222 Z	222KD	1222F	222-SF	7522	222P	19 APL
6224-Z	120	215	40	11.400	6224 Z	-	224-SF	-	-	224P	-
6226-Z	130	230	40	13.800	6226 Z	-	-	-	-	-	-


TWO SHIELDS

6200-ZZ	10	30	9	.080	6200.ZZ	200KDD	1200FF	200-SFF	77500	200PP	04 APPL
6201-ZZ	12	32	10	.090	6201.ZZ	201KDD	1201FF	201-SFF	77501	201PP	03 APPL
6202-ZZ	15	35	11	.100	6202.ZZ	202KDD	1202FF	202-SFF	77502	202PP	02 APPL
6203-ZZ	17	40	12	.150	6203.ZZ	203KDD	1203FF	203-SFF	77503	203PP	01 APPL
6204-ZZ	20	47	14	.250	6204.ZZ	204KDD	1204FF	204-SFF	77504	204PP	1 APPL
6205-ZZ	25	52	15	.290	6205.ZZ	205KDD	1205FF	205-SFF	77505	205PP	2 APPL
6206-ZZ	30	62	16	.440	6206.ZZ	206KDD	1206FF	206-SFF	77506	206PP	3 APPL
6207-ZZ	35	72	17	.640	6207.ZZ	207KDD	1207FF	207-SFF	77507	207PP	4 APPL
6208-ZZ	40	80	18	.810	6208.ZZ	208KDD	1208FF	208-SFF	77508	208PP	5 APPL
6209-ZZ	45	85	19	.900	6209.ZZ	209KDD	1209FF	209-SFF	77509	209PP	6 APPL
6210-ZZ	50	90	20	1.020	6210.ZZ	210KDD	1210FF	210-SFF	77510	210PP	7 APPL
6211-ZZ	55	100	21	1.340	6211.ZZ	211KDD	1211FF	211-SFF	77511	211PP	8 APPL
6212-ZZ	60	110	22	1.730	6212.ZZ	212KDD	1212FF	212-SFF	77512	212PP	9 APPL
6213-ZZ	65	120	23	2.180	6213.ZZ	213KDD	1213FF	213-SFF	77513	213PP	10 APPL
6214-ZZ	70	125	24	2.360	6214.ZZ	214KDD	1214FF	214-SFF	77514	214PP	11 APPL
6215-ZZ	75	130	25	2.600	6215.ZZ	215KDD	1215FF	215-SFF	77515	215PP	12 APPL
6216-ZZ	80	140	26	3.090	6216.ZZ	216KDD	1216FF	216-SFF	77516	216PP	13 APPL
6217-ZZ	85	150	28	3.950	6217.ZZ	217KDD	1217FF	217-SFF	77517	217PP	14 APPL
6218-ZZ	90	160	30	4.740	6218.ZZ	218KDD	1218FF	218-SFF	77518	218PP	15 APPL
6219-ZZ	95	170	32	5.780	6219.ZZ	-	1219FF	219-SFF	77519	219PP	16 APPL
6220-ZZ	100	180	34	6.920	6220.ZZ	-	1220FF	220-SFF	77520	220PP	17 APPL
6221-ZZ	105	190	36	8.160	6221.ZZ	-	1221FF	221-SFF	77521	221PP	18 APPL
6222-ZZ	110	200	38	9.610	6222.ZZ	-	1222FF	222-SFF	77522	222PP	19 APPL
6224-ZZ	120	215	40	11.400	6224.ZZ	-	-	224-SFF	-	224PP	-
6226-ZZ	130	230	40	13.800	6226.ZZ	-	-	-	-	-	-


NOTE:
 1.) C/3 and C/4 internal clearances are available on all of the above sizes.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



One Shield With Snap Ring ZNR



Two Shields With Snap Ring ZZNR

DEEP GROOVE BALL BEARINGS - ONE SHIELD WITH SNAP RING

MVB No.	Dimensions					Approx. Wgt. (lbs.)	Interchange				
	(Metric)		(Inch)				FAF	FAG STEYR	MRC	ND	SKF
	d	D	B	f	c						
6200-ZNR	10	30	9	.134	.053	.080	-	6200 ZNR	200-SFG	47500	6200 ZNR
6201-ZNR	12	32	10	.134	.053	.090	201KDG	6201 ZNR	201-SFG	47501	6201 ZNR
6202-ZNR	15	35	11	.134	.053	.100	202KDG	6202 ZNR	202-SFG	47502	6202 ZNR
6203-ZNR	17	40	12	.134	.053	.150	203KDG	6203 ZNR	203-SFG	47503	6203 ZNR
6204-ZNR	20	47	14	.149	.053	.250	204KDG	6204 ZNR	204-SFG	47504	6204 ZNR
6205-ZNR	25	52	15	.149	.053	.290	205KDG	6205 ZNR	205-SFG	47505	6205 ZNR
6206-ZNR	30	62	16	.203	.075	.440	206KDG	6206 ZNR	206-SFG	47506	6206 ZNR
6207-ZNR	35	72	17	.203	.075	.640	207KDG	6207 ZNR	207-SFG	47507	6207 ZNR
6208-ZNR	40	80	18	.203	.075	.810	208KDG	6208 ZNR	208-SFG	47508	6208 ZNR
6209-ZNR	45	85	19	.203	.075	.900	209KDG	6209 ZNR	209-SFG	47509	6209 ZNR
6210-ZNR	50	90	20	.235	.106	1.020	210KDG	6210 ZNR	210-SFG	47510	6210 ZNR
6211-ZNR	55	100	21	.235	.106	1.340	211KDG	6211 ZNR	211-SFG	47511	6211 ZNR
6212-ZNR	60	110	22	.235	.106	1.730	212KDG	6212 ZNR	212-SFG	47512	6212 ZNR
6213-ZNR	65	120	23	.281	.122	2.180	-	6213 ZNR	213-SFG	47513	6213 ZNR
6214-ZNR	70	125	24	.281	.122	2.360	214KDG	6214 ZNR	214-SFG	47514	6214 ZNR
6215-ZNR	75	130	25	.281	.122	2.600	-	6215 ZNR	215-SFG	47515	6215 ZNR
6216-ZNR	80	140	26	.313	.122	3.090	-	6216 ZNR	216-SFG	47516	6216 ZNR
6217-ZNR	85	150	28	.313	.122	3.950	-	6217 ZNR	-	47517	6217 ZNR
6218-ZNR	90	160	30	.313	.122	4.740	-	6218 ZNR	-	47518	-
6219-ZNR	95	170	32	.361	.138	5.780	-	6219 ZNR	-	47519	-
6220-ZNR	100	180	34	.361	.138	6.920	-	6220 ZNR	-	47520	-
6221-ZNR	105	190	36	.361	.138	8.160	-	-	-	-	-
6222-ZNR	110	200	38	.361	.138	9.610	-	-	-	47522	-
6224-ZNR	120	215	40	.361	.138	12.100	-	-	-	-	-
6226-ZNR	130	230	40	.433	.177	13.800	-	-	-	-	-

TWO SHIELDS WITH SNAP RING


6200-ZZNR	10	30	9	.134	.053	.080	200KDDG	6200-2ZNR	200-SFFG	477500	6200 2ZNR
6201-ZZNR	12	32	10	.134	.053	.090	201KDDG	6201-2ZNR	201-SFFG	477501	6201 2ZNR
6202-ZZNR	15	35	11	.134	.053	.100	202KDDG	6202-2ZNR	202-SFFG	477502	6202 2ZNR
6203-ZZNR	17	40	12	.134	.053	.150	203KDDG	6203-2ZNR	203-SFFG	477503	6203 2ZNR
6204-ZZNR	20	47	14	.149	.053	.250	204KDDG	6204-2ZNR	204-SFFG	477504	6204 2ZNR
6205-ZZNR	25	52	15	.149	.053	.290	205KDDG	6205-2ZNR	205-SFFG	477505	6205 2ZNR
6206-ZZNR	30	62	16	.203	.075	.440	206KDDG	6206-2ZNR	206-SFFG	477506	6206 2ZNR
6207-ZZNR	35	72	17	.203	.075	.640	207KDDG	6207-2ZNR	207-SFFG	477507	6207 2ZNR
6208-ZZNR	40	80	18	.203	.075	.810	208KDDG	6208-2ZNR	208-SFFG	477508	6208 2ZNR
6209-ZZNR	45	85	19	.203	.075	.900	209KDDG	6209-2ZNR	209-SFFG	477509	6209 2ZNR
6210-ZZNR	50	90	20	.235	.106	1.020	210KDDG	6210-2ZNR	210-SFFG	477510	6210 2ZNR
6211-ZZNR	55	100	21	.235	.106	1.340	211KDDG	6211-2ZNR	211-SFFG	477511	6211 2ZNR
6212-ZZNR	60	110	22	.235	.106	1.730	-	6212-2ZNR	212-SFFG	477512	6212 2ZNR
6213-ZZNR	65	120	23	.281	.122	2.180	213KDDG	6213-2ZNR	213-SFFG	477513	6213 2ZNR
6214-ZZNR	70	125	24	.281	.122	2.360	-	6214-2ZNR	-	477514	6214 2ZNR
6215-ZZNR	75	130	25	.281	.122	2.600	-	6215-2ZNR	-	477515	6215 2ZNR
6216-ZZNR	80	140	26	.313	.122	3.090	-	6216-2ZNR	-	477516	6216 2ZNR
6217-ZZNR	85	150	28	.313	.122	3.950	-	6217-2ZNR	-	477517	6217 2ZNR
6218-ZZNR	90	160	30	.313	.122	4.740	-	6218 2ZNR	-	477518	-
6219-ZZNR	95	170	32	.361	.138	5.780	-	6219 2ZNR	-	477519	-
6220-ZZNR	100	180	34	.361	.138	6.920	-	6220 2ZNR	-	477520	-
6221-ZZNR	105	190	36	.361	.138	8.160	-	-	-	-	-
6222-ZZNR	110	200	38	.361	.138	9.610	-	-	-	477522	-
6224-ZZNR	120	215	40	.361	.138	12.100	-	-	-	-	-
6226-ZZNR	130	230	40	.433	.177	13.800	-	-	-	-	-

NOTE:

- 1.) When the shield is required on the same side as the snap ring use ZNBR suffix.
- 2.) C/2 and C/3 internal clearance is available on all of the above sizes.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



One Seal
RS

DEEP GROOVE BALL BEARINGS - ONE SEAL


MVB No.	Dimensions (Metric Inch)			Approx. Wgt. (lbs.)	Interchange					
	d	D	B		FAG SKF STEYR	FAF	FED	MRC	ND	NH
6200-RS	10	30	9	.080	6200 RS	200P	1200R	200-SZ	Z9500	200N
6201-RS	12	32	10	.090	6201 RS	201NP	1201R	201-SZ	Z9501	201N
6201/008-RS	.5000	32	10	.090	-	-	-	-	-	-
6201/13-RS	13	32	10	.090	-	-	-	-	-	-
6202-2RS	15	35	11	.100	6202 RS	202NP	1202R	202-SZ	Z9502	202K
6202/008-RS	.5000	35	11	.100	-	-	-	-	-	-
6202/010-RS	.6250	35	11	.100	-	-	-	-	-	-
6202/16-RS	16	35	11	.100	-	-	-	-	-	-
6203-RS	17	40	12	.150	6203 RS	203P	1203R	203-SZ	Z9503	203K
6203/012-RS	.7500	40	12	.150	-	-	-	-	-	-
6204-RS	20	47	14	.250	6204 RS	204P	1204R	204-SZ	Z9504	204N
6204-012-RS	.7500	47	14	.250	-	-	-	-	-	-
62/22-RS	22	50	14	.280	-	-	-	-	-	-
6205-RS	25	52	15	.290	6205 RS	205P	1205R	205-SZ	Z9505	205K
6205/100-RS	1.0000	52	15	.290	-	-	-	-	-	-
62/28-RS	28	58	16	.380	-	-	-	-	-	-
6206-RS	30	62	16	.440	6206 RS	206P	1206R	206-SZ	Z9506	206K
62/32-RS	32	65	17	.490	-	-	-	-	-	-
6207-RS	35	72	17	.640	6207 RS	207P	1207R	207-SZ	Z9507	207K
6208-RS	40	80	18	.810	6208 RS	208P	1208R	208-SZ	Z9508	-
6209-RS	45	85	19	.900	6209 RS	209P	1209R	209-SZ	Z9509	-
6210-RS	50	90	20	1.020	6210 RS	210P	1210R	210-SZ	Z9510	-
6211-RS	55	100	21	1.340	6211 RS	211P	1211R	211-SZ	Z9511	-
6212-RS	60	110	22	1.730	6212 RS	212P	1212R	212-SZ	Z9512	-
6213-RS	65	120	23	2.180	6213 RS	213P	1213R	-	-	-
6214-RS	70	125	24	2.360	6214 RS	214P	1214R	-	-	-
6215-RS	75	130	25	2.600	6215 RS	215P	1215R	-	-	-
6216-RS	80	140	26	3.060	6216 RS	-	-	-	-	-
6217-RS	85	150	28	3.950	6217 RS	-	-	-	-	-
6218-RS	90	160	30	4.940	6218 RS	-	-	-	-	-
6219-RS	95	170	32	6.100	6219 RS	-	-	-	-	-
6220-RS	100	180	34	6.920	6220 RS	-	-	-	-	-
6222-RS	110	200	38	9.610	6222 RS	-	-	-	-	-
6224-RS	120	215	40	11.400	6224 RS	-	-	-	-	-
6226-RS	130	230	40	13.200	6226 RS	-	-	-	-	-

NOTE:


- 1.) C/3 and C/4 internal clearances are available on all of the above sizes.
- 2.) Inch bore sizes - FAF and ND bearings are shielded.



MVB Power-Star Bearing Co.
 Url:www.mvbbearing.com
 Email:vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel:+86-592-523 0986
 Fax:+86-592-376 1975



One Seal With Snap Ring RSNR



Two Seals With Snap Ring 2RSNR

DEEP GROOVE BALL BEARINGS - ONE SEAL WITH SNAP RING

MVB No.	Dimensions					Approx. Wgt. (lbs.)	Interchange				
	(Metric)		(Inch)				FAF	FAG STEYR	MRC	ND	SKF
	d	D	B	f	c						
6200-RSNR	10	30	9	.134	.053	.080	-	6200 RSNR	-	Z49500	6200 RSNR
6201-RSNR	12	32	10	.134	.053	.090	-	6201 RSNR	201-SZG	Z49501	6201 RSNR
6202-RSNR	15	35	11	.134	.053	.100	-	6202 RSNR	202-SZG	Z49502	-
6203-RSNR	17	40	12	.134	.053	.150	-	6203 RSNR	203-SZG	Z49503	6203 RSNR
6204-RSNR	20	47	14	.149	.053	.250	-	6204 RSNR	204-SZG	Z49504	6204 RSNR
6205-RSNR	25	52	15	.149	.053	.290	-	6205 RSNR	205-SZG	Z49505	6205 RSNR
6206-RSNR	30	62	16	.203	.075	.440	-	6206 RSNR	206-SZG	Z49506	6206 RSNR
6207-RSNR	35	72	17	.203	.075	.640	-	6207 RSNR	207-SZG	Z49507	6207 RSNR
6208-RSNR	40	80	18	.203	.075	.810	-	6208 RSNR	-	Z49508	-
6209-RSNR	45	85	19	.203	.075	.900	-	6209 RSNR	-	Z49509	-
6210-RSNR	50	90	20	.235	.106	1.020	-	6210 RSNR	-	Z49510	-
6211-RSNR	55	100	21	.235	.106	1.340	-	6211 RSNR	-	Z49511	6211 RSNR
6212-RSNR	60	110	22	.235	.106	1.730	-	6212 RSNR	-	Z49512	6212 RSNR
6213-RSNR	65	120	23	.281	.122	2.180	-	6213 RSNR	-	-	6213 RSNR
6214-RSNR	70	125	24	.281	.122	2.360	-	6214 RSNR	214-SZG	-	-
6215-RSNR	75	130	25	.281	.122	2.600	-	6215 RSNR	-	-	6215 RSNR
6216-RSNR	80	140	26	.313	.122	3.090	-	6216 RSNR	-	-	6216 RSNR
6217-RSNR	85	150	28	.313	.122	3.950	-	6217 RSNR	-	-	-
6218-RSNR	90	160	30	.313	.122	4.740	-	6218 RSNR	-	-	-
6219-RSNR	95	170	32	.361	.138	5.780	-	6219 RSNR	-	-	-
6220-RSNR	100	180	34	.361	.138	6.920	-	6220 RSNR	-	-	-
6221-RSNR	105	190	36	.361	.138	8.160	-	-	-	-	-
6222-RSNR	110	200	38	.361	.138	9.610	-	-	-	-	-
6224-RSNR	120	215	40	.361	.138	12.100	-	-	-	-	-
6226-RSNR	130	230	40	.433	.177	13.800	-	-	-	-	-

TWO SEALS WITH SNAP RING

6200-2RSNR	10	30	9	.134	.053	.080	200PPG	6200-2RSNR	200-SZZG	Z499500	6200 2RSNR
6201-2RSNR	12	32	10	.134	.053	.090	201PPG	6201-2RSNR	201-SZZG	Z499501	6201 2RSNR
6202-2RSNR	15	35	11	.134	.053	.100	202PPG	6202-2RSNR	202-SZZG	Z499502	6202 2RSNR
6202/008-2RSNR	.5000	35	11	.134	.053	.100	-	-	-	-	-
6202/010-2RSNR	.6250	35	11	.134	.053	.100	-	-	-	-	-
6203-2RSNR	17	40	12	.134	.053	.150	203PPG	6203-2RSNR	203-SZZG	Z499503	6203 2RSNR
6203/010-2RSNR	.6250	40	12	.134	.053	.150	-	-	-	-	-
6204-2RSNR	20	47	14	.149	.053	.250	204PPG	6204-2RSNR	204-SZZG	Z499504	6204 2RSNR
6205-2RSNR	25	52	15	.149	.053	.290	205PPG	6205-2RSNR	205-SZZG	Z499505	6205 2RSNR
6205/100-2RSNR	1.0000	52	15	.149	.053	.290	-	-	-	-	-
6206-2RSNR	30	62	16	.203	.075	.440	206NPPG	6206-2RSNR	206-SZZG	Z499506	6206 2RSNR
6207-2RSNR	35	72	17	.203	.075	.640	207NPPG	6207-2RSNR	207-SZZG	Z499507	6207 2RSNR
6208-2RSNR	40	80	18	.203	.075	.810	208NPPG	6208-2RSNR	208-SZZG	Z499508	6208 2RSNR
6209-2RSNR	45	85	19	.203	.075	.900	209NPPG	6209-2RSNR	209-SZZG	Z499509	6209 2RSNR
6210-2RSNR	50	90	20	.235	.106	1.020	210NPPG	6210-2RSNR	210-SZZG	Z499510	6210 2RSNR
6211-2RSNR	55	100	21	.235	.106	1.340	211NPPG	6211-2RSNR	211-SZZG	Z499511	6211 2RSNR
6212-2RSNR	60	110	22	.235	.106	1.730	212NPPG	6212-2RSNR	212-SZZG	Z499512	6212 2RSNR
6213-2RSNR	65	120	23	.281	.122	2.180	213NPPG	6213-2RSNR	213-SZZG	-	6213 2RSNR
6214-2RSNR	70	125	24	.281	.122	2.360	-	6214-2RSNR	214-SZZG	-	6214 2RSNR
6215-2RSNR	75	130	25	.281	.122	2.600	-	6215-2RSNR	215-SZZG	-	6215 2RSNR
6216-2RSNR	80	140	26	.313	.122	3.090	-	6216-2RSNR	-	-	6216 2RSNR
6217-2RSNR	85	150	28	.313	.122	3.950	-	6217-2RSNR	-	-	6217 2RSNR
6218-2RSNR	90	160	30	.313	.122	4.740	-	6218-2RSNR	-	-	-
6219-2RSNR	95	170	32	.361	.138	5.780	-	6219-2RSNR	-	-	-
6220-2RSNR	100	180	34	.361	.138	6.920	-	6220-2RSNR	-	-	-
6221-2RSNR	105	190	36	.361	.138	8.160	-	-	-	-	-
6222-2RSNR	110	200	38	.361	.138	9.610	-	-	-	-	-
6224-2RSNR	120	215	40	.361	.138	12.100	-	-	-	-	-
6226-2RSNR	130	230	40	.433	.177	13.800	-	-	-	-	-

NOTE:

- 1.) When the seal is required on the same side as the snap ring use RSNBR suffix.
- 2.) C/2 and C/3 internal clearance is available on all of the above sizes.