


Self-aligning Ball Bearings


调心球轴承



XMVB® XMVB Power-Star Bearing Co.
 Url: www.mvbbearing.com
 Email: vivy@mvbbearing.com
 mvbbearing@gmail.com
 Tel: +86-592-523 0986
 Fax: +86-592-376 1975



Cylindrical Bore
Open



Tapered Bore - 1:12
Open

SELF-ALIGNING BALL BEARINGS

No.	Dimensions (Metric)		B	Approx. Wgt. lbs	ADR	Interchange
	d	D				
SAV-3	3	10	4	.010	V 3	
SAV-4	4	12	4	.010	V 4	
SAV-5	5	13	4	.020	V 5	
SAV-6	6	15	5	.020	V 6	
SAV-7	7	17	5	.030	V 7	
SAV-8	8	19	6	.030	V 8	
SAV-9	9	20	6	.040	V 9	

SELF-ALIGNING BALL BEARINGS

Cylindrical Bore	Tapered Bore	No.	Dimensions (Metric)			Approx. Wgt. (lbs.)	Interchange						
			d	D	B		FAG	FAF	FED	MRC	SKF	STEYR	
		13300	5	19	6	.020	135TV	-	-	-	135	135	-
		13301	6	19	6	.020	126TV	-	-	-	126	126	-
		13302	7	22	7	.040	127TV	-	-	-	125	127	-
		13303	8	22	7	.040	108TV	-	-	-	108	108	-
		13304	9	26	8	.050	129TV	-	-	-	129	129	-
		1200	10	30	9	.080	1200TV	-	-	1200 SA	1200 E	1200 E	1200 E/TG
		1201	12	32	10	.090	1201TV	-	-	1201 SA	1201 E	1201 E	1201 E/TG
		1202	15	35	11	.110	1202TV	-	-	1202 SA	1202 E	1202 E	1202 E/TG
		1203	17	40	12	.170	1203TV	-	-	1203 SA	1203 E	1203 E	1203 E/TG
	1204K	1204	20	47	14	.270	1204TV	L-204	-	1204 SA	1204 E	1204 E	1204 E/TG
	1205K	1205	25	52	15	.320	1205TV	L-205	-	1205 SA	1205 E	1205 E	1205 E/TG
	1206K	1206	30	62	16	.490	1206TV	L-206	-	1206 SA	1206 E	1206 E	1206 E/TG
	1207K	1207	35	72	17	.720	1207TV	L-207	-	1207 SA	1207 E	1207 E	1207 E/TG
	1208K	1208	40	80	18	.920	1208TV	L-208	-	1208 SA	1208 E	1208 E	1208 E/TG
	1209K	1209	45	85	19	1.030	1209TV	L-209	-	1209 SA	1209 E	1209 E	1209 E/TG
	1210K	1210	50	90	20	1.160	1210TV	L-210	-	1210 SA	1210 E	1210 E	1210 E/TG
	1211K	1211	55	100	21	1.550	1211TV	L-211	-	1211 SA	1211 E	1211 E	1211 E/TG
	1212K	1212	60	110	22	1.980	1212TV	L-212	-	1212 SA	1212 E	1212 E	1212 E/TG
	1213K	1213	65	120	23	2.540	1213TV	L-213	-	1213 SA	1213 E	1213 E	1213 E/TG
	1214K	1214	70	125	24	2.780	1214TV	-	-	1214 SA	1214	1214	1214
	1215K	1215	75	130	25	3.000	1215TV	L-215	-	1215 SA	1215	1215	1215
	1216K	1216	80	140	26	3.680	1216TV	-	-	1216 SA	1216	1216	1216
	1217K	1217	85	150	28	4.560	1217TV	-	-	1217 SA	1217	1217	1217
	1218K	1218	90	160	30	5.560	1218	-	-	1218 SA	1218	1218	1218
	1219K	1219	95	170	32	6.840	1219	-	-	1219 SA	1219	1219	1219
	1220K	1220	100	180	34	8.980	1220	-	-	1220 SA	1220	1220	1220
	1221K	1221	105	190	36	10.600	1221	-	-	-	-	1221	1221
	1222K	1222	110	200	38	12.540	1222	-	-	1222 SA	1222	1222	1222
	1224 M	1224 MK	120	215	42	17.000	1224M	-	-	-	1224	1224	1224 M
	1226 M	1226 MK	130	230	46	20.350	1226M	-	-	-	1226	1226	-
	1228 M	1228 MK	140	250	50	26.680	1228M	-	-	-	-	-	-
	1230 M	1230 MK	150	270	54	35.000	1230M	-	-	-	-	-	-

NOTE:

- 1.) 1201 thru 1222 also available with machined bronze cage - "M" suffix.
- 2.) 1224 not equal to SKF (U.S.A.) width.
- 3.) Above sizes also available in C/2, C/3, C/4 and C/5 internal clearances.
- 4.) Allowable misalignment 4°.