



www.mvbbearing.com

MVB Bearings No.	Shaft Dia		Dimensions inch/mm														Basic Load Ratings (KN)		Weight (Kg)
	(in.)	(mm)	D	Bi	Be	n	m	W	O	T	an	G	Y	X	S	ds	Dynamic Cr	Static Cor	
SSER201-8	1/2																		
SSER201-9	9/16																		
SSER202-10	5/8		1.8504	0.2189	0.6252	0.4055	0.8150	1.1417	0.1575	0.0421	0.0969	0.1969	2.0748	0.6402	1.6252	1/4-28UNF	9.88	6.2	0.27
SSER203-11	11/16																		
SSER204-12	3/4																		
SSER201		12																	
SSER202		15	47	31	16	10.3	20.7	29	4	1.07	2.46	5	52.7	16.3	41.3	M6x1.0			0.23
SSER203		17																	
SSER204		20																	0.22
SSER205-13	13/16																		
SSER205-14	7/8		2.0472	1 3/8	3/4	33/64	55/64	1 3/8	13/64	0.0421	0.0969	0.2205	2.2795	5/8	1 55/64	1/4-28UNF	10.78	6.98	0.28
SSER205-15	15/16																		
SSER205-16	1																		
SSER205		25	52	25	19	13.1	21.8	35	5	1.07	2.46	5.6	57.9	16	47	M6x1.0			
SSER206-17	1 1/16																		
SSER206-18	1 1/8		2.4409	1 1/2	7/8	5/8	7/8	19/32	7/32	0.0650	0.1291	0.2205	2.6654	5/8	2 5/32	1/4-28UNF	14.97	10.04	0.38
SSER206-19	1 3/16																		
SSER206-20		30	62	38	22	15.9	22.2	40	5.5	1.65	3.28	5.6	67.7	16	53.6	M6x1.0			
SSER206																			
SSER207-20	1 1/4																		
SSER207-21	1 5/16		2.8346	11/16	15/16	11/16	1.0000	55/64	7/32	0.0650	0.1291	0.2520	3.0945	23/32	2 9/16	5/16-24UNF	19.75	13.67	0.56
SSER207-22	1 3/8																		
SSER207-23	1 7/16																		
SSER207		35	72	43	24	17.5	25.4	47	5.5	1.65	3.28	6.4	78.6	18	62.2	M8x1.0			
SSER208-24	1 1/2		3.1496	15/19	3/32	3/4	3/16	2 1/16	1/4	0.0650	0.1291	0.3150	3.4094	53/64	2 53/64	5/16-24UNF	22.71	15.94	0.87
SSER208-25	1 9/16																		
SSER208		40	80	49	28	19	30.2	52	6	1.65	3.28	8	86.6	21	69.6	M8x1.0			
SSER209-26	1 5/8		3.3465	15/16	3/32	3/4	3/16	19/64	1/4	0.0650	0.1291	0.3150	3.606299	53/64	3 1/16	3/8-24UNF	24.36	17.71	0.95
SSER209-27	1 11/16																		
SSER209-28	1 3/4																		
SSER209		45	85	49	28	19	30.2	58	6	1.65	3.28	8	91.6	21	77	M10x1.25			
SSER210-29	1 13/16																		
SSER210-30	1 7/8		3.5433	2 1/32	1 1/8	3/4	1 9/32	2 15/32	19/64	3/32	0.1291	0.3740	3.8031	15/16	5 7/32	3/8-24UNF	26.98	19.84	1.03
SSER210-31	1 15/16																		
SSER210-32	2																		
SSER210		50	90	52	29	19	32.6	62	7.5	2.3	3.28	9.5	96.6	24	80.5	M10x1.25			
SSER211-32	2																		
SSER211-33	2 1/16		3.937	2 3/16	1 3/16	7/8	1 5/16	2 23/32	19/64	3/32	0.1291	0.3740	4.1969	15/16	3 9/16	3/8-24UNF	33.37	25.11	1.21
SSER211-34	2 1/8																		
SSER211-35	2 3/16																		
SSER211		55	100	55.6	22	22.2	33.4	69	7.5	2.41	3.28	9.5	106.6	24	88.4	M10x1.25			
SSER212-36	2 1/4																		
SSER212-37	2 5/16		4.3307	2 9/16	1 1/4	1.0000	1 9/16	2 31/32	19/64	3/32	0.1291	0.4370	4.5906	1 5/32	3 15/16	3/8-24UNF	36.74	29.97	1.68
SSER212-38	2 3/8																		
SSER212-39	2 7/16																		
SSER212		60	110	65	31.8	25.4	39.6	75	7.5	2.41	3.28	11.1	116.6	29	97.1	M10x1.25			
SSER213-40	2 1/2		4.7244	2 9/16	1 3/8	1.0000	1 9/16	3 1/4	5/16	7/64	0.1638	0.4370	5.0079	1 17/64	4 13/32	3/8-24UNF	41.58	35.15	2.3
SSER213-41	2 9/16																		
SSER213		65	120	65.1	35	25.4	39.6	82.5	8	2.78	4.16	11.1	127.2	32	111	M10x1.25			
SSER214-42	2 5/8																		
SSER214-43	2 11/16		4.9213	2 3/4	1 3/8	1 1/16	1 11/16	3 7/16	5/16	7/64	0.1638	0.4724	5.2165	1 17/64	4 13/32	7/16-20UNF	48.75	40.56	2.8
SSER214-44	2 3/4																		
SSER214		70	125	70	35	27	43	87	8	2.78	4.16	12	132.5	32	111	M12x1.25			
SSER215-45	2 13/16																		
SSER215-46	2 7/8		5.1181	3 1/16	1 1/2	1 5/16	1 3/4	3 21/32	3/8	7/64	0.1638	0.4724	5.5000	1 17/64	4 5/8	7/16-20UNF	53.74	47.84	3.56
SSER215-47	2 15/16																		
SSER215-48	3																		
SSER215		75	130	77.8	38	33	44	92	9.5	2.78	4.16	12	139.7	32	117	M12x1.25			